

AZ sections are continuous through the web with the interlocks located symmetrically on each side of the neutral axis, this positively influences the section modulus.


- Proven qualities of the Larsen interlock
- Extremely competitive section modulus to mass ratio
- Increased inertia for reduced deflection
- No interlock shear reduction factors that do apply to U piles
- Wide profiles, resulting in improved installation performance
- Improved corrosion performance with increased steel thickness at the critical corrosion points

Section	Width b mm	Height h mm	Thickness		Sectional Area cm ² /m	Coating Area* m ² /m of Wall	Mass		Section Modulus cm ³ /m	Moment of Inertia cm ⁴ /m
			t mm	s mm			kg/m Single Pile	kg/m ² of Wall		
AZ-800 Sections										
AZ 18-800	800	449	8.5	8.5	129	1.30	80.7	101	1840	41320
AZ 20-800	800	450	9.5	9.5	141	1.30	88.6	111	2000	45050
AZ 22-800	800	451	10.5	10.5	153	1.30	96.4	120	2165	48790
AZ 23-800	800	474	11.5	9.0	151	1.32	94.6	118	2330	55260
AZ 25-800	800	475	12.5	10.0	163	1.32	102.6	128	2500	59410
AZ 27-800	800	476	13.5	11.0	176	1.32	110.5	138	2670	63570
AZ-750 Sections										
AZ 28-750	750	509	12.0	10.0	171	1.41	100.8	134	2810	71540
AZ 30-750	750	510	13.0	11.0	185	1.41	108.8	145	3005	76670
AZ 32-750	750	511	14.0	12.0	198	1.41	116.7	156	3200	81800
AZ-770 Sections										
AZ 12-770	770	344	8.5	8.5	120	1.20	72.6	94	1245	21430
AZ 13-770	770	344	9.0	9.0	126	1.20	76.1	99	1300	22360
AZ 14-770	770	345	9.5	9.5	132	1.20	79.5	103	1355	23300
AZ 14-770-10/10	770	345	10.0	10.0	137	1.20	82.9	108	1405	24240
AZ-700 Sections										
AZ 12-700	700	314	8.5	8.5	123	1.22	67.7	97	1205	18880
AZ 13-700	700	315	9.5	9.5	135	1.22	74.0	106	1305	20540
AZ 13-700-10/10	700	316	10.0	10.0	140	1.22	77.2	110	1355	21370
AZ 14-700	700	316	10.5	10.5	146	1.22	80.3	115	1405	22190
AZ 17-700	700	420	8.5	8.5	133	1.33	73.1	104	1730	36230
AZ 18-700	700	420	9.0	9.0	139	1.33	76.5	109	1800	37800
AZ 19-700	700	421	9.5	9.5	146	1.33	80.0	114	1870	39380
AZ 20-700	700	421	10.0	10.0	152	1.33	83.5	119	1945	40960
AZ 24-700	700	459	11.2	11.2	174	1.38	95.7	137	2430	55820
AZ 26-700	700	460	12.2	12.2	187	1.38	102.9	147	2600	59720
AZ 28-700	700	461	13.2	13.2	200	1.38	110.0	157	2760	63620
AZ 36-700N	700	499	15.0	11.2	216	1.47	118.6	169	3590	89610
AZ 38-700N	700	500	16.0	12.2	230	1.47	126.4	181	3795	94840
AZ 40-700N	700	501	17.0	13.2	244	1.47	134.2	192	3995	100080
AZ 42-700N	700	499	18.0	14.0	259	1.46	142.1	203	4205	104930
AZ 44-700N	700	500	19.0	15.0	273	1.46	149.9	214	4405	110150
AZ 46-700N	700	501	20.0	16.0	287	1.46	157.7	225	4605	115370
AZ 48-700	700	503	22.0	15.0	288	1.46	158.5	226	4755	119650
AZ 50-700	700	504	23.0	16.0	303	1.46	166.3	238	4955	124850
AZ 52-700	700	505	24.0	17.0	317	1.46	174.1	249	5155	130140

* One side excluding inside of interlocks

- Notes:
- Piles typically supplied threaded together as double piles from the mill, either crimped or uncrimped
 - Corner sections with Larsen interlocks suitable for these profiles can be supplied

The information contained in this document is provided for general reference only and may be inaccurate or out of date. Under no circumstances, will J Steel Australasia Pty Ltd or its related bodies corporate be liable for any errors or omissions in any information presented in or for any loss or damages of any kind which might be incurred as a result of the information contained in this document.



AZ sections are continuous through the web with the interlocks located symmetrically on each side of the neutral axis, this positively influences the section modulus.

- Proven qualities of the Larsen interlock
- Extremely competitive section modulus to mass ratio
- Increased inertia for reduced deflection
- No interlock shear reduction factors that do apply to U piles
- Wide profiles, resulting in improved installation performance
- Improved corrosion performance with increased steel thickness at the critical corrosion points

Section	Width b mm	Height h mm	Thickness		Sectional Area cm ² /m	Coating Area* m ² /m of Wall	Mass		Section Modulus cm ³ /m	Moment of Inertia cm ⁴ /m
			t mm	s mm			kg/m Single Pile	kg/m ² of Wall		

AZ Classic Sections

AZ 18	630	380	9.5	9.5	150	1.23	74.4	118	1800	34200
AZ 18-10/10	630	381	10.0	10.0	157	1.23	77.8	123	1870	35540
AZ 26	630	427	13.0	12.2	198	1.41	97.8	155	2600	55510